

North Carolina State Building Code

1958
Edition

Published by
The North Carolina Building Code Council
and the
North Carolina Department of Insurance
Room 300, Labor Building
Raleigh, NC

NORTH CAROLINA STATE BUILDING CODE

*Adopted by the North Carolina Building Code
Council in accordance with Act
of the General Assembly of
1957, Chapter 1138*

Published by
THE NORTH CAROLINA BUILDING CODE COUNCIL
Staff and Offices
Located at
NORTH CAROLINA DEPARTMENT OF INSURANCE
Room 300, Labor Building
Raleigh, N. C.

FOREWORD

North Carolina has been a pioneer in the field of statewide building and Fire Prevention regulations which have been enacted for the protection of the public. The Building Laws passed in 1903 and 1905 created a Building Code for materials and methods of construction in use at that time.

A meeting was held on November 28, 1931, at North Carolina State College to discuss the formulation of a modern State Building Code. Several State and local officials and representatives of several agencies and organizations in the construction industry attended. Mr. Sherwood Brockwell was Chairman, Mr. Harry Barton was Vice-Chairman and Mr. W. G. Geile was Secretary of this first Building Code Committee which formulated the first North Carolina Building Code during the next two years.

The General Assembly of 1933 created a Building Code Council and authorized it to, in cooperation with the Commissioner of Insurance, prepare and adopt a Building Code. The first North Carolina Building Code received the approval of the official Building Code Council and the Commissioner of Insurance in 1935 and was printed that same year. The General Assembly of 1941 ratified and adopted this edition, which was known as the 1936 Edition.

A few modifications of this printed Code were made from time to time by the Building Code Council and accepted by the Commissioner of Insurance.

A general revision to bring the Code up to date was considered in order at meeting held on November 12, 1952, attended by representatives from several State organizations interested in the construction industry. At the suggestion of Albert L. Haskins, Jr., A. I. A., then Chairman of the Building Code Council, a preliminary draft was prepared by the staff of the Department of Insurance and copies were mailed to the various organizations interested in the construction industry, including the North Carolina Society of Engineers; North Carolina Chapter of the American Institute of Architects; North Carolina Branch of the Associated General Contractors of America; State Board of Health; North Carolina Chapter of the Society of Civil Engineers; the North Carolina Association of Plumbing and Heating Contractors; North Carolina League of Municipalities; Division of Schoolhouse Planning; Budget Bureau and the North Carolina Fire Insurance Rating Bureau. Comments and criticisms were received from several of these organizations and open meetings were held in the office of the Commissioner of Insurance together with representatives of these organizations.

By a unanimous vote on June 19, 1953, the Building Code Council adopted the draft as revised and recommended its acceptance by the Commissioner of Insurance. On the same date

the Commissioner of Insurance accepted the recommendations of the Council and ordered the final draft printed.

The 1957 Legislature rewrote the 1933 Act and reorganized and expanded the Building Code Council. This 1958 Edition is a reprint of the 1953 Edition together with all amendments to date. It also contains several pertinent Building laws and standards and regulations of several State Agencies for the convenience of the users of the Code.

The Code is presented with the hope that its use will protect the public from dangerous and unsanitary buildings and will provide Architects and Engineers a set of minimum standards to follow in designing buildings. The Building Code Council has authority to make changes in the Code when the wider use of materials and methods comply with safety standards set forth in the Laws. From time to time, there will be modifications and changes in the Code.

BUILDING CODE COUNCIL

Members of the Building Code Council are as follows:

Chairman, A. G. ODELL, JR., FAIA
Architect, Charlotte

Vice-Chairman, T. C. COOKE, PE
Mechanical Engineer, Durham

H. B. FOSTER, PE
Structural Engineer
Greensboro

S. W. SANDERS, JR.
Building Inspector
Wilmington

R. E. VICK, PE
Department of Property Control
Raleigh

J. C. SMITH, JR.
General Contractor
Leaksville

A. H. JEFFRESS,
Attorney
Kinston

R. F. BOOTH, PE
Electrical Engineer
Raleigh

VERNE G. MOSER
Plumbing and Heating Contractor
Asheville

INSURANCE DEPARTMENT

By Statute the Commissioner of Insurance has general supervision of the administration and enforcement of the North Carolina Building Code and the Engineering Division serves as the staff for the Building Code Council. Officials of the Insurance Department are:

CHARLES F. GOLD
Commissioner of Insurance

N. E. CANNADY, FAIEE
Chief Engineer and
Chief Deputy State Fire Marshal

KERN E. CHURCH, SFPE
Engineer and Deputy State Fire Marshal
and Secretary, North Carolina Building
Code Council

CONTENTS

	<i>Page</i>
NORTH CAROLINA GENERAL STATUTES	
Chapter 14—Criminal Law	1
Chapter 58—Insurance Laws	1
Section 58-193—Plans of Buildings Owned by State, County and City to be Submitted to Insurance Department.....	1
Chapter 69—Fire Protection—Hotels	2
Article I—Investigation of Fires, Inspection of Premises.....	2
Article II—Fire Escapes	2
Article IV—Hotels; Safety Provisions.....	5
Chapter 87—Contractors	9
Chapter 133—Public Works	10
Chapter 143—State Departments, Institutions and Commissions.....	11
Article 9—Building Code	11
Chapter 160—Municipal Corporations	20
Article 11—Regulations of Buildings.....	20
Article 18—Powers of Municipal Corporations.....	27
ARTICLE I—ADMINISTRATION	
Section 102. Scope	37
Section 103. Approval of Plans and Building Permits Required.....	38
Section 104. Enforcement	40
Section 105.2. Unsafe Buildings and Structures.....	41
Section 106. Building Code Council	42
Section 107. Hearings and Appeals.....	42
Section 108. Violation and Penalties	43
Section 109. Procedural Rules for Appeals to Building Code Council from Enforcement Agencies.....	43
Section 110. Procedural Rules for Hearings Before Building Code Council on Proposed Amendments.....	45
ARTICLE II—DEFINITIONS	
Section 200. Definitions	47
ARTICLE III—CLASSIFICATION OF OCCUPANCIES AND CONSTRUCTION	
Section 300. Classification of Occupancies	56
301. Classification of Construction.....	58
ARTICLE IV—GENERAL RESTRICTIONS	
Section 400. Zoning Restrictions	59
401. Restrictions on Construction Within the Fire Limits.....	59
402. Special Occupancy Requirements.....	60
403. Height Restrictions	62
404. Area Restrictions	62
405. Street Encroachments	68

CONTENTS—Continued

	<i>Page</i>
ARTICLE V—LIGHT AND VENTILATION	
Section 500. General	71
501. Rooms	71
502. Windows	74
503. Vent Shafts	74
504. Ventilating Skylights	75
505. Mechanical Ventilation	75
506. Courts	75
ARTICLE VI—MEANS OF EGRESS	
Section 600. Application of Article	77
601. General	77
602. Number of Exits	78
603. Location	80
604. Interior Stairways	81
605. Fire Towers	86
606. Horizontal Exits	86
607. Exterior Stairways	87
608. Ramps	88
609. Exit Hallways	88
610. Doorways	88
611. Maintenance	90
612. Modification of Exit Requirements	91
613. Special Requirements for Location of Exits	93
ARTICLE VII—REQUIREMENTS FOR TYPES OF CONSTRUCTION	
Section 700. Compliance	94
701. Fireproof Construction	94
702. Semifireproof Construction	99
703. Heavy Timber Construction	101
704. Ordinary Construction	104
705. Noncombustible Construction	107
706. Wood Frame Construction	109
707. Unprotected Metal Construction	110
ARTICLE VIII—MATERIALS AND DESIGN LOADS	
Section 800. Materials	111
801. Tests	111
802. Weights of Building Materials	112
803. Live Loads	114
804. Wind Pressure	116
ARTICLE IX—GENERAL CONSTRUCTION REQUIREMENTS	
Section 900. Workmanship	118
901. Working Stresses, General	118
902. Excavations	118
903. Foundations General	119

CONTENTS—Continued

	<i>Page</i>
904. Soil Bearing Values.....	120
905. Foundation Walls	121
906. Pile Foundations	122
907. Masonry	123
908. Reinforced Concrete	133
909. Fire Walls and Party Walls.....	141
910. Parapets	143
911. Chases and Recesses.....	144
912. Wall Veneering	144
913. Reinforced Gypsum Concrete	146
914. Structural Steel and Cast Iron.....	148
915. Light Gauge Steel Structural Members.....	153
916. Steel Joists	154
917. Wood Structural Members	156
918. Fire Partitions	162
919. Glass Blocks	162
920. Protection of Exterior Openings.....	164
921. Shafts	165
922. Roofing	167
923. Pent Houses and Roof Structures.....	168
924. Non-Bearing Partition Construction.....	170
925. Basement Partitions	170
926. Basement Cellings	170
927. Floors on the Ground.....	170
928. Floor Drainage	171
929. Glass Floor Lights.....	171
930. Lathing and Plastering.....	171

ARTICLE X—CHIMNEYS, FLUES AND VENTS

Section 1000. Definitions	172
1001. Flues, General	172
1002. Chimneys	173
1003. Metal Smokestacks	177
1004. Cupola Chimneys	178
1005. Raising Adjoining Chimneys.....	178
1006. Flues and Vents for Gas Appliances.....	179

ARTICLE XI—HEAT PRODUCING APPLIANCES, HEATING, VENTILATING, AIR CONDITIONING, BLOW- ER AND EXHAUST SYSTEMS

Section 1100. Installation Standards	183
1101. Boiler and Furnace Rooms.....	183
1102. Drying Rooms	183
1103. Ash Pits	184
1104. Special Requirements	184

CONTENTS—Continued

	<i>Page</i>
ARTICLE XII—PLACES OF ASSEMBLY, THEATRES, MOTION PICTURE THEATRES, ASSEMBLY HALLS AND GARAGES	
Section 1200. General	185
1201. Stage	189
1202. Enclosures for Motion Picture Projectors.....	192
1203. Use of Roofs	194
1204. Garages	194
ARTICLE XIII—SAFEGUARDS DURING CONSTRUCTION	
Section 1300. General	198
1301. Scaffolds	198
1302. Sidewalk Sheds	198
1303. Temporary Fence or Barricade.....	199
1304. Hoists	199
1305. Flooring	200
1306. Floor Openings	201
1307. Roofs and Skylights of Adjoining Buildings.....	201
1308. Stair Facilities	201
1309. Fire Protection	201
1310. Heating	202
1311. Welding and Cutting	203
1312. Watchman	204
1313. Storage of Materials	204
1314. Disposal of Waste.....	204
1315. Warning Lights	204
1316. Basement Drainage	205
1317. Lighting	205
1318. Temporary Wiring	205
1319. Sanitation	205
1320. Accidents	205
1321. Demolition	205
ARTICLE XIV—ELEVATORS, MOVING STAIRWAYS AND AMUSEMENT DEVICES	
Section 1400. General	207
1401. Repairs	207
1402. Design and Equipment	207
1403. Riding on Freight Elevators Restricted.....	208
1404. Amusement Devices	209
1405. Certificate	209
1406. Inspection	209
1407. Accidents	210
1408. Operation	211
1409. Fire Department Use	211

CONTENTS—Continued

	<i>Page</i>
ARTICLE XV—MISCELLANEOUS EQUIPMENT	
Section 1500. Lighting	212
1501. Gas Piping	212
1502. Shut-off Valves	213
1503. Openings Around Pipes and Ducts.....	213
ARTICLE XVI—ELECTRICAL INSTALLATIONS.....	
	216
ARTICLE XVII—FIRE EXTINGUISHING AND ALARM EQUIPMENT	
Section 1700. General	217
1701. Standpipes	217
1702. Sprinkler Equipments	220
1703. Automatic Fire Alarm Systems.....	223
1704. Amusement Park Protection	223
ARTICLE XVIII—SIGNS AND OUTDOOR DISPLAY STRUCTURES	
Section 1800. General	224
1801. Alterations	224
1802. Construction	225
ARTICLE XIX—SAFETY TO LIFE REQUIREMENTS FOR HERETOFORE ERECTED BUILDINGS	
Section 1900. Certificate of Occupancy.....	227
1901. Determining and Posting of Floor Loads.....	227
1902. Means of Egress.....	227
1903. Roofing Repairs	232
1904. Chimneys, Flues and Smokestacks.....	232
1905. Heat Producing Appliances	232
1906. Fire Extinguishing Equipment.....	232

Please refer to Fly Sheet in Front of Book for the Following

ARTICLE XX—PLUMBING

FIRE RESISTANCE RATINGS (ARTICLE XXI)

CODE FOR HEAT PRODUCING APPLIANCES (ARTICLE XXII)

GENERAL INDEX

**APPENDIX I—NORTH CAROLINA UNIFORM RESIDENTIAL BUILD-
ING CODE**

**APPENDIX II—SANITATION REGULATIONS OF STATE BOARD OF
HEALTH**

APPENDIX III—ELEVATOR CODE

APPENDIX IV—BOILER CODE

**APPENDIX V—REGULATIONS OF INTERDEPARTMENTAL BUILDING
REGULATION COMMITTEE**

**NORTH CAROLINA STATE BUILDING CODE
ARTICLE I**

ADMINISTRATION AND PROCEDURE

SECTION 100—TITLE: These rules and regulations shall be known as the 1958 Edition of the North Carolina State Building Code, may be cited as such and will be referred to hereinafter as this Code. (See G. S. 143-138a)

SECTION 101—PURPOSE: The purpose of the Code is to provide certain minimum standards, provisions and requirements for safe and stable design, methods of construction and uses of materials in buildings and/or structures hereafter erected, constructed, enlarged, altered, repaired, moved, converted to other uses or demolished and to regulate the equipment, maintenance, use and occupancy of all buildings and/or structures. All regulations contained in the North Carolina State Building Code shall have a reasonable and substantial connection with the public health, safety, morals, or general welfare, and their provisions shall be construed liberally to those ends. (See G. S. 143-138c)

SECTION 102—SCOPE:

1. New Buildings and Additions—Exemptions. The Code shall apply to all new buildings, structures and additions thereto wherever they might be situated in the State provided, however, that such regulations shall not apply to the following types of buildings unless the governing body of the municipality or the county wherein such buildings are located shall by vote adopt a resolution making the regulations applicable to one or more such types of buildings:

- (a) Dwellings; and outbuildings used in connection therewith;
- (b) Apartment buildings used exclusively as the residence of not more than two families;
- (c) Temporary buildings or sheds used exclusively for construction purposes, not exceeding twenty feet in any direction and not used for living quarters.

This Code shall not apply to farm buildings located outside any municipality.

2. Alterations to Existing Buildings:

(a) This Code shall apply to all alterations which affect the structural strength, fire hazards, exits, lighting or sanitary conditions of any building except those exempted in Section 102.1. Within the fire limits (as defined in G. S. Section 160-124) of cities and towns where this article applies, as established and defined, no frame or wooden building shall be hereafter erected, altered, repaired or removed except upon the permit of the build-

Section 103

ing inspector, approved by the Insurance Commissioner. (See G. S. 160-124, G. S. 160-127 and G. S. 160-128)

(b) If, within any period of twelve months, alterations or repairs costing in excess of fifty percent of the then physical value of the buildings are made to an existing building, such building shall be made to conform to the requirements of this code for new buildings, except that for buildings located in fire districts the provisions of Section 102.2(a) and 401 shall also apply.

(c) If an existing building is damaged by fire or otherwise in excess of fifty percent of its then physical value before such damage is repaired, it shall be made to conform to the requirements of this code for new buildings.

(d) If the cost of such alterations or repairs, or the amount of such damage, is more than twenty-five but not more than fifty percent of the then physical value of the building, the portions to be altered or repaired shall be made to conform to the requirements of this code for new buildings to such extent as the Building Inspector may determine.

(e) For the purpose of this section physical value of the building shall be determined by the Building Inspector.

3. Change of Use: This Code shall apply to all buildings which are to be devoted to a new use for which the requirements of this Code are in any way more stringent than the requirements covering the previous use of the building.

4. Local Regulations: This Code shall not be understood to limit the powers of cities, villages and towns to make or enforce additional or more stringent requirements and regulations, provided the same do not conflict with this Code or any revision of this Code.

NOTE: Every municipality is authorized to adopt, for its own benefit:

(a) Regulations covering the construction of dwellings.

(b) Other fire-preventive and sanitary regulations which cannot be reasonably included in this Code.

Local Codes must be approved by the Building Code Council as per Section 143-138e before they become effective. (See G. S. 143-138 b and e; and G. S. 160-237)

SECTION 103 — APPROVAL OF PLANS AND BUILDING PERMITS REQUIRED:

1. Plans Approved by Insurance Commissioner:

(a) For every building classified as Public or Institutional or as a Hotel or designed to accommodate one hundred or more people, plans shall be prepared and copies thereof furnished the Insurance Commissioner for his approval before work is begun on such building. (See G. S. 143-139(d); Section 300, 602-e and 612(d))

Section 103

(b) For every other building costing \$10,000 or more and/or designed to accommodate one hundred or more persons, except those exempted in Section 102.1, plans may be required to be furnished the Insurance Commissioner in order that the provisions of this article may be adhered to.

(c) The plans and specifications so prepared shall be complete in every detail so that the work will comply with the provisions as set forth in this Code and shall be constructed under the supervision of a competent superintendent or inspector, in accordance with the plans and specifications. (See G. S. 143-139d; G. S. 58-193 and G. S. 69-10)

2. Building Permits Required from Local Inspectors:

(a) **New Buildings:** Before a building is begun the owner of the property shall apply to the inspector for a permit to build. This permit shall be given in writing and shall contain a provision that the building shall be constructed according to the requirements of the Building Code. Statement of compliance with the Code shall be included with the permit. No permit shall be issued unless the plans and specifications are identified by the name and address of the author thereof, and where the General Statutes of North Carolina require that plans for certain types of construction be prepared only by a registered architect or a registered engineer, no permit shall be issued unless such plans and specifications bear the North Carolina seal of a registered architect or of a registered engineer. As the building progresses the inspector shall make as many inspections as may be necessary to satisfy him that the building is being constructed according to the provisions of this law. As soon as the building is completed the owner shall notify the inspector who shall proceed at once to inspect the said building and determine whether or not the building has been properly constructed in accordance with the Building Code. If, in the opinion of the Building Inspector, the building meets the requirements of the building code the inspector shall then issue to the owner of the building a certificate which shall state that he has complied with the requirements of the building code as to that particular building, giving description and locality and street number if numbered. The inspector shall keep his record so that it will show readily by reference all such buildings as are approved. The inspector shall report to the Insurance Commissioner every person neglecting to secure such permit and certificate, and also bring the matter before the mayor, recorder or municipal court for their attention and action. (See G. S. 160-126, G. S. 87-14, Chapter 83 and Chapter 89 of the General Statutes)

(b) **Existing Buildings:** A permit is required from the building inspector to repair, alter, move, demolish or add to an existing building or structure. (See Section 102.2)

Section 104

(c) *Special Permits*: A special permit is required for alterations and repairs to wood frame buildings located inside the fire limits. (See G. S. 160-128)

(d) *Occupancy Permits*: Before a building is changed from one occupancy to another occupancy the owner shall obtain from the inspector a permit for such change in occupancy. (See G. S. 69-4, G. S. 69-12, G. S. 69-13, G. S. 160-143, 144)

3. *Plans to be Kept at Building*: When permit has been issued for the construction of any building, the owner or contractor shall keep at the building a set of plans and specifications that have been approved by authority having jurisdiction in order that any building inspector, whether state or city, may ascertain when he visits a building under construction, whether the construction is in accordance with the plans. .

4. *Other Approvals*: Section 103.1 of this Code shall not be construed to repeal any existing provisions of law requiring plans and specifications for building construction and work connected therewith to be filed with any state or local board or department, and to be previously approved by said state or local board or department. (Please see Table I Appendix V of State Interdepartment Building Regulation Committee in back of Code).

SECTION 104—ENFORCEMENT

1. *Duty of Commissioner of Insurance*: By Statute the Insurance Commissioner has general supervision of the administration and enforcement of the North Carolina Building Code in cooperation with local building inspectors. (See G. S. 143-139d and G. S. 69-13)

2. Duties of Building Inspector:

(a) *Office Created*: There is created by Statute the office of building inspector in all cities and towns of 1000 or more in population according to the last U. S. census whose duty shall be to enforce the North Carolina State Building Code. In towns where a building inspector has not been appointed in compliance with G. S. 160-118, the Chief of Fire Department has the statutory duty of enforcing the code as per G. S. 160-118. (See G. S. 160-118, G. S. 160-120 and G. S. 160-154)

(b) Inspections Required:

1. *New Building, Repairs, Alterations, Removing, Demolition and Additions to Existing Buildings*: After issuing proper permit for new buildings, repairs or alterations or additions, the building inspector shall make as many inspections as may be necessary to satisfy him that the building is being constructed according to the provisions of this code.

2. *Periodic Inspections*: Inspections of existing buildings are required to determine their compliance with the Building Code

Section 105

and to determine whether they meet the minimum safety to life requirements. (160-143, 160-149)

3. **Change of Occupancy:** When an existing building is to be converted to another occupancy, the building inspector shall make an inspection of such building to see that it is in compliance with the safety requirements of the code. (See G. S. 160-126, G. S. 160-142, G. S. 160-143 and G. S. 160-149)

(c) *Records of Inspections:* The local inspector shall keep the following record: A record indexed and kept so that it will show readily by reference all such buildings as are approved; that is, name and residence of owner, location of building, how it is to be occupied, date of inspection, what defects found and when remedied and date of building certificate; also a record which shall show the date of every general inspection, defects discovered and when remedied; also a record which shall show the date, circumstances and origin of every fire that occurs, name of owner and occupant of the building in which fire originates, the kind and value of property destroyed or damaged (except where such records are kept by other departments); also a record of inspection of electrical wiring, heating and plumbing and certificate issued. (See G. S. 160-144)

SECTION 105—POWERS OF COMMISSIONER OF INSURANCE AND BUILDING INSPECTORS:

1. **Right of Entry:** The Insurance Commissioner or the Building Inspector has the statutory right at all reasonable hours for the purpose of examination, to enter into or upon all buildings in their jurisdiction. (See G. S. 69-4, G. S. 69-13, G. S. 160-143)

2. **Condemnation of Unsafe Buildings:**

(a) *Unsafe Buildings Condemned:* By Statute every building which shall appear to the inspector to be especially dangerous because of its liability to fire or in case of fire by reason of bad condition of walls, overloaded floors, defective construction, inadequate exits, decay or other causes shall be held to be unsafe, and the inspector shall affix a notice of the dangerous character of the structure to a conspicuous place on the exterior wall of said building. No building now or hereafter built shall be altered, repaired or moved, until it has been examined and approved by the inspector as being in a good and safe condition to be altered as proposed, and the alteration, repair or change so made shall conform to the provisions of the law. (See G. S. 160-149, G. S. 160-151 and G. S. 69-35)

(b) *Punishment for Allowing Unsafe Building to Stand is Provided by Law as Follows:* If the owner of any building which has been condemned as unsafe and dangerous by any local inspector, after being notified by the inspector in writing of the unsafe and dangerous character of such building, shall permit

Sections 106—107

the same to stand or continue in that condition, he shall forfeit and pay a fine of not less than ten nor more than fifty dollars for each day such building continues after such notice. (See G. S. 160-152)

(c) If after ninety days from legal notice from the inspector, the owner or owners of a building which has been condemned fails to answer such notice of condemnation, the Chief of the Fire Department or the local Building Inspector, may, with and by a two-thirds vote of the City Council, order such building removed, with reasonable expense incurred by such removal charged against the property. (See G. S. 160-151 and 160-152 and G. S. 69-35)

SECTION 106—BUILDING CODE COUNCIL

1. **Building Code Council Created:** There is by statute created a State Building Code Council composed of nine members appointed by the Governor consisting of one registered architect, one licensed general contractor, one registered engineer practicing structural engineering, one registered engineer practicing mechanical engineering, one registered engineer practicing electrical engineering, one licensed plumbing and heating contractor, one municipal building inspector, a representative of the public who is not a member of the building construction industry, and a representative of the engineering staff of a State agency charged with approval of plans of State owned buildings. (See G. S. 143-136a)

2. **Officers:** The Council shall elect from its appointed members a Chairman and Vice-Chairman. Officers shall serve for a period of two years from the date of election or until their successors are elected. (See G. S. 143-137a)

3. **Duties:** The Building Code Council shall have the duty of adopting and amending the North Carolina State Building Code and hearing appeals from the decision of an enforcement agency. (See G. S. 143-138 a, d, and e; and G. S. 143-141)

4. **Meetings:** The Building Code Council shall meet regularly the second Tuesday in January and July. Special meetings may be called by the Chairman. Any five members of the Council shall constitute a quorum. (See G. S. 143-137b)

5. **Staff and Personnel:** The Division of Engineering of the Department of Insurance shall serve as the staff for the Council. (See G. S. 143-137c)

SECTION 107—HEARINGS AND APPEALS

1. **Hearings and Appeals before the Commissioner of Insurance:** Any person desiring to raise any questions under the

North Carolina State Building Code shall be entitled to a full hearing before the Insurance Commissioner upon proper request in writing by any such person. (See G. S. 143-140 and G. S. 69-13)

2. Hearings and Appeals to Building Code Council:

(a) *Hearings for Amending the Building Code:* Any person, firm or corporation desiring to amend the Building Code shall file a request for hearing with the Council in accordance with rules as outlined in Section 110. (See G. S. 143-138, a, c, d)

(b) *Appeals from the Decision of an Enforcement Agency:* Any person desiring to take an appeal to the Building Code Council from the decision of a State enforcement agency must file such appeal within thirty days after such decision giving written notice to the Council as per procedural rules as outlined in Section 109. (See G. S. 143-141)

3. Appeal to Court: By Statute a person may appeal directly to the Superior Court of the County in which the proposed building is to be situated with or without an appeal to the Building Code Council. (See G. S. 143-141d)

SECTION 108—VIOLATION AND PENALTIES ARE PROVIDED BY STATUTE AS FOLLOWS:

Any person who shall be adjudged to have violated the North Carolina State Building Code shall be guilty of a misdemeanor and shall upon conviction be liable to a fine not to exceed \$50.00 for each offense. Each thirty days that such violation continues shall constitute a separate and distinct offense. (See G. S. 14-68; 69-36 and 69-37; 87-14; 143-138h; 160-119; 160-125 and 160-129; 160-150 and 160-151 and 160-153)

SECTION 109—PROCEDURAL RULES FOR APPEALS TO THE BUILDING CODE COUNCIL FROM THE ENFORCEMENT AGENCIES.—The following procedural rules shall apply and must be complied with when any appeal is taken by any aggrieved party from the decision of any enforcement agency (as defined in G. S. 143-139) to the Building Code Council:

Rule 1—Time of Notice—Any person wishing to appeal from the decision of an enforcement agency to the Building Code Council shall give a written Notice of Appeal as follows:

(a) The original and eleven copies of said notice shall be filed not later than 30 days from the date of the decision of the enforcement agency with the Building Code Council, c/o Division of Engineering, Department of Insurance, 300 Labor Building, Raleigh, North Carolina.

Section 109

(b) The staff of the Building Code Council shall immediately forward one copy of said notice to the enforcement agency from which the appeal is taken.

(c) The time within which notice is to be filed, shall be computed by excluding the first and including the last day. If the last day is Saturday, Sunday or a legal holiday, it must be excluded.

Rule 2—Form of Notice—Whenever Notice of Appeal is given as provided by these rules, said notice shall be legibly printed, typewritten or mimeographed and shall contain the following information:

(a) The name of the party or parties taking the appeal;

(b) The name of the enforcement agency and the date of the decision from which the appeal is taken;

(c) The decision from which the appeal is taken must be set forth in full in the Notice of Appeal, or a copy of said decision must be attached to all copies of the Notice of Appeal;

(d) The contentions and allegations of fact of the party or parties taking the appeal must be set forth in full in a clear and concise manner with particular reference to the section or sections of the North Carolina State Building Code in controversy;

(e) The original notice shall be signed by the party or parties filing same. No notarization or verification is required.

Rule 3—Time for Hearing—Upon the proper filing of an appeal in accordance with these rules, the Chairman of the Building Code Council shall cause the appeal to be heard by the Council within a reasonable time.

Rule 4—Notice to Appellant—The Chairman of the Building Code Council shall cause all appeals to be docketed for hearing and shall fix the time and place for said hearing and shall cause not less than ten days notice in writing, of the time and place of the hearing on the appeal to be given to the appellant, the enforcement agency from which the appeal is taken and all members of the Council.

Rule 5—Dismissal—The Council shall, upon motion of the enforcement agency or on its own motion, dismiss all appeals for the following reasons:

(a) Not prosecuted by the appellant; and

Section 110

- (b) All appeals wherein the Notice of Appeal has not been filed in accordance with these Rules; and
- (c) For lack of jurisdiction.

SECTION 110 — PROCEDURAL RULES FOR HEARINGS BEFORE THE BUILDING CODE COUNCIL ON PROPOSED AMENDMENTS TO THE NORTH CAROLINA STATE BUILDING CODE.—The following procedural rules shall apply when any citizen, State agency, or political subdivision of the State makes application to the Building Code Council requesting that the North Carolina State Building Code be revised or amended pursuant to G. S. 143-138 (d) :

Rule 1—Request for Hearing—Any citizen, State agency, or political subdivision of the state requesting a hearing before the Building Code Council for the above purposes shall submit a written request as follows :

- (a) An original and ten copies of said request for hearing shall be filed with the Building Code Council, c/o The Division of Engineering, Department of Insurance, 300 Labor Building, Raleigh, North Carolina.
- (b) The staff of the Building Code Council shall immediately forward one copy of said request to each member of the Building Code Council.

Rule 2—Form of Request for Hearing—Each request shall be legibly printed, typewritten, or mimeographed and shall contain the following information :

- (a) Name, address and basis of interest of party or parties requesting hearing;
- (b) The proposed amendment to the North Carolina State Building Code must be set forth in full, and the request shall contain explicit reference to the affected section or sections of the Building Code;
- (c) The request shall state, in support of the proposed amendment or amendments, the reasons for proposing the amendment or amendments;
- (d) The proposed amendment or amendments shall comply with the standards set forth in G. S. 143-138 (c) and reference to the particular standards involved shall be set forth in the request for hearing.
- (e) The original request for a hearing shall be signed by the party or parties or their duly authorized agent submitting same.

Section 110

Rule 3—Time of Hearing—Upon the proper filing of a request for hearing in accordance with these rules, the Chairman of the Building Code Council shall cause a hearing to be held within a reasonable time not to exceed six months; said hearing shall be open to the public.

Rule 4—Notice of Hearing—The Chairman of the Building Code Council shall fix the time and place for said public hearing and shall cause notice of the hearing to be given as follows:

(a) Notice in writing to the party or parties or their duly authorized agents requesting the hearing not less than fifteen days prior to the hearing.

(b) Notice of public hearing by publication as required by G. S. 143-138 (a);

(c) Not less than ten days notice in writing to all members of the Building Code Council.

Rule 5—Improper Filing of Request for Hearing—When a request for hearing is filed under this Section other than in accordance with these Rules, the staff of the Building Code Council shall notify the applicant of proper procedure to follow.

The standards referred to in G. S. 143-138(c) include the following nationally recognized Building Codes: (1) The National Building Code of the National Board of Fire Underwriters; (2) the Southern Standard Building Code of the Southern Building Code Congress; (3) the Uniform Building Code of the Pacific Coast Building Officials Conference; (4) the Basic Building Code of the Building Officials Conference of America, Inc.; (5) the Building Exits Code of the National Fire Protection Association. Other standards dealing with special equipment are as follows: the National Electric Code; the American Standard Safety Code for Elevators, Dumbwaiters, and Escalators; Standards of the National Board of Fire Underwriters for the Installation of Gas Piping and Gas Appliances in Buildings, and standards promulgated by the American Standards Association, Underwriters' Laboratories, Inc., and similar national agencies engaged in research concerning strength of materials, safe design and other factors bearing upon health and safety.

ARTICLE II

SECTION 200. DEFINITIONS.

(a). Unless otherwise expressly stated, the following terms shall, for the purpose of this code, have the meaning indicated in this section.

(b). Words used in the present tense include the future; words in the masculine gender include the feminine and neuter; the singular number includes the plural and the plural the singular.

(c). Where terms are not defined in this section, they shall have their ordinarily accepted meanings or such as the context may imply.

Alley means any public space or thoroughfare less than 20 feet in width which has been dedicated or deeded for public use.

Alteration, as applied to a building or structure, means a change or rearrangement in the structural parts or in the exit facilities; or an enlargement, whether by extending on a side or by increasing in height; or the moving from one location or position to another; the term "alter" in its various moods and tenses and its participial forms, refers to the making of an alteration.

Amusement device means a mechanically operated device which is used to convey persons in any direction as a form of amusement.

Apartment means a room, or a suite of two or more rooms, in a residence building occupied as the home or residence of an individual, family or household.

Approved, as applied to a material, device or mode of construction, means approved by the city building inspector under the provisions of this code, or by other authority designated by law to give approval in the matter in question.

Area, as applied to a form of construction, means an uncovered subsurface space adjacent to a building.

Area, as applied to the dimensions of a building, means the maximum horizontal projected area of the building at grade.

ACI means American Concrete Institute.

ASA means the American Standards Association.

ASTM means the American Society for Testing Materials.

Automatic, as applied to a fire door or other opening protective, means normally held in an open position and automatically closed

Section 200

by a releasing device that is actuated by abnormal high temperature or by a predetermined rate of rise in temperature.

Automatic fire alarm system means a system which automatically detects a fire condition and actuates a fire alarm signal device.

Basement means a story with 40 per cent or more of its cubical contents below finished grade.

Brick means a solid masonry unit having a shape approximating a rectangular prism, not larger than 12 by 4 by 4 inches. A brick may be made of burned clay or shale, of lime and sand, of cement and suitable aggregates, or of fire clay or other approved materials.

Building means a combination of materials to form a construction that is safe and stable, and adapted to permanent or continuous occupancy for public, institutional, residence, business or storage purposes; the term "building" shall be construed as if followed by the words "or part thereof." For the purposes of this code, each portion of a building separated from other portions by a fire wall shall be considered as a separate building.

Building line means the line, established by law, beyond which a building shall not extend, except as specifically provided by law.

Building inspector means the officer or other designated authority charged with administration and enforcement of this code, or his duly authorized representative.

Concrete means a mixture of portland cement, aggregate and water, of such materials, proportions, and manipulation as to give specified results;

average concrete means a mixture of one part of portland cement and not more than 6 parts of aggregate proportioned by volume, with the necessary water;

controlled concrete means concrete where the materials are scientifically selected, graded and proportioned to give specified results;

reinforced concrete means a portland cement concrete in which steel is embedded in such a manner that the two materials act together in resisting forces.

Court means an open, uncovered and unoccupied space within the lot lines of a lot, and includes a yard.

Curb level means the elevation of the street grade as established in accordance with law;

referring to a building, it means the elevation at that point of the street grade that is opposite the center of the wall nearest to and facing the street line;

Section 200

referring to an excavation, it means the elevation at that point of the street grade which is nearest to the point of the excavation under consideration.

Dead load means the weight of walls, partitions, floors, roofs and all other permanent construction of a building.

Display sign means a structure that is arranged, intended, designed or used as an advertisement, announcement or direction; and includes a sign, sign screen, billboard and advertising devices of every kind.

Dwelling means a building occupied exclusively for residence purposes and having not more than two apartments, or as a boarding or rooming house serving not more than 5 persons with meals or sleeping accommodations or both.

Elevator means a device within or in connection with a building used for carrying persons or things upward or downward; and includes dumbwaiter and similar devices;

freight elevator means an elevator designed and used for the carrying of freight and such persons only as are necessary for its safe operation or the handling of freight carried by it;

passenger elevator means an elevator designed and used for carrying persons.

Fire door means a door and its assembly, so constructed and assembled in place as to give protection against the passage of fire.

Fire partition—see "Walls."

Fire resistance rating means the time in hours that the material or construction will withstand the standard fire exposure as determined by a fire test made in conformity with the "Standard Methods of Fire Tests of Building Construction and Materials," ASTM E 119-47.

Fire retardant ceiling means a ceiling construction which has been proved by test as satisfactory for use as ceiling protection for a floor or roof construction which has a fire resistance rating of not less than one hour.

Fire retardant treated lumber means lumber which has been treated by a pressure impregnation process to give a flame spread classification of 50 or less according to the method for the "Fire Hazard Classification of Building Materials" of Underwriters' Laboratories, Inc., and which is shown to be so classified by a certificate or label issued by Underwriters' Laboratories, Inc.

Fire walls—see "Wall."

Freight elevator—see "Elevator."

Section 200

Garage means a building, shed or enclosure, or a part thereof, in which a motor vehicle containing a flammable fluid in its fuel storage tank, is stored, housed, kept or repaired.

Gasoline service station means a structure, building or premise or any portion thereof where a flammable fluid for retail supply to motor vehicles is stored, housed, or sold.

Grade, with reference to a building, means, when the curb level has been established, the mean elevation of the curb level opposite those walls that are located on, or parallel with and within 15 feet of, street lines; or, when the curb level has not been established, or all the walls of the building are more than 15 feet from street lines; "grade" means the mean elevation of the ground adjoining the building on all sides.

Gypsum mortar when used in the laying of unit construction means a mixture of one part neat gypsum and not more than three parts of clean, sharp, well-graded sand by weight.

Habitable room means a room occupied by one or more persons for living, eating or sleeping; and includes kitchens serving apartments or individual households, but does not include bathrooms, toilet compartments, laundries, serving and storage pantries, corridors, basement and other spaces that are not used frequently or during extended periods.

Height as applied to a building, means the vertical distance from grade to the highest finished roof surface in the case of flat roofs, or to a point at the average height of roofs having a pitch of more than one foot in 4½ feet; "height" of a building in stories does not include basements, except that in school buildings of ordinary, noncombustible or wood frame construction, the basement shall be deemed a story when used for purposes other than storage or heating.

height, as applied to a court, means the vertical distance from the level of the floor of the lowest story served by that court to the level under consideration;

height, as applied to a story means the vertical distance from top to top of two successive tiers of floor beams or finished floor surfaces;

height, as applied to a wall, means the vertical distance to the top measured from the foundation wall, or from a girder or other immediate support of such wall.

Hereafter means after the time that this code becomes effective.

Heretofore means before the time that this code becomes effective.

Section 200

Hollow masonry unit means a masonry unit whose net cross-sectional area in any plane parallel to the bearing surface is less than 75 per cent of its gross cross-sectional area measured in the same plane.

Live load means all loads except dead load.

Lot means a portion or parcel of land considered as a unit, devoted to a certain use or occupied by a building or a group of buildings that are united by a common interest or use, and the customary accessories and open spaces belonging to the same.

Lot line means a line dividing one lot from another, or from a street or other public space.

Masonry means brick, stone, plain concrete, hollow block, solid block or other similar building units or materials, or combinations of them, bonded together with mortar. Reinforced concrete is

Section 200

- (c) Materials made up of noncombustible material as defined in (a) together with combustible components in such form that cross-sections of the material in any plane present a similar composition, and having a surface flame spread rating not higher than 25 without evidence of continued progressive combustion. Examples: certain insulation materials as, blocks of cellular glass, boards of glass fiber, slabs of wood excelsior impregnated with portland cement.
- (d) Materials, other than as described in (b), made up of layers with no layer having a surface flame spread rating higher than 25 without evidence of continued progressive combustion. Examples: certain sandwich type materials.

Occupied, as applied to a building, shall be construed as though followed by the words "or intended, arranged or designed to be occupied."

Owner includes his duly authorized agent or attorney, a purchaser, devisee, fiduciary, and a person having a vested or contingent interest in the property in question.

Passenger elevator—see "Elevator."

Pent house means an enclosed structure other than a roof structure, located on the roof, extending not more than twelve feet above a roof and used primarily for living or recreational accommodations.

Person includes corporation and copartnership as well as individual.

Place of assembly means a room or space in which provision is made for the seating of one hundred or more persons for religious, recreational, educational, political, social or amusement purposes or for the consumption of food or drink. Such room or space shall include any occupied connecting room or space in the same story, or in a story or stories above or below, where entrance is common to the rooms or spaces.

Prefabricated means composed of sections or panels fabricated prior to erection on the building foundation.

Repair means the replacement of existing work with the same kind of material used in the existing work not including additional work that would affect the structural safety of the building, or that would affect or change required exit facilities, or that would affect a vital element of an elevator, plumbing, gas piping, wiring or heating installation, or that would be in violation of a provision of law or ordinance.

Required means required by some provision of this code.

Roof means the roof slab or deck with its supporting members.

Section 200

Roofing means the covering applied to the roof for weather resistance, fire resistance, or appearance.

Roof structure means a structure above the roof of any part of a building enclosing a stairway, tank, elevator machinery or ventilating apparatus, or such part of a shaft as extends above the roof and not housing living or recreational accommodations.

Self closing, as applied to a fire door or other opening protective, means normally closed and equipped with an approved device which will insure closing after having been opened for use.

Shaft means a vertical opening or passage through two or more floors of a building or through floors and roof.

Solid masonry means masonry consisting of solid masonry units laid contiguously with the joints between the units filled with mortar, or consisting of plain concrete.

Solid masonry unit means a masonry unit whose net cross-sectional area in every plane parallel to the bearing surface is 75 per cent or more of its gross cross-sectional area measured in the same plane.

Sprinklered means equipped with an approved automatic sprinkler system properly maintained.

Stairway means one or more flights of stairs and the necessary landings and platforms connecting them, to form a continuous and uninterrupted passage from one story to another in a building or structure.

Story means that part of a building comprised between a floor and the floor or roof next above. A mezzanine shall be considered a story if it exceeds 25 per cent of the area of the floor immediately below.

Street means any public thoroughfare, street, avenue, boulevard, park, lane, terrace, concourse or space 20 feet or more in width which has been dedicated or deeded to the public for public use.

Street line means a lot line dividing a lot from a street.

Structural clay tile means a hollow masonry unit composed of burned clay, shale, fireclay or mixtures thereof and having parallel cells.

Structure means a combination of materials to form a construction that is safe and stable; including among others, buildings, stadiums, gospel and circus tents, reviewing stands, platforms, stagings, observation towers, radio towers, water tanks and towers, trestles, piers, wharves, sheds, coal bins, fences and display

Section 200

signs; the term structure shall be construed as if followed by the words "or part thereof."

Walls:

bearing wall means a wall which supports any vertical load in addition to its own weight;

cavity wall means a wall built of masonry units or of plain concrete, or a combination of these materials, so arranged as to provide an air space within the wall, and in which the inner and outer parts of the wall are tied together with metal ties;

curtain wall means a non-bearing wall between columns or piers and which is not supported by girders or beams;

faced wall means a wall in which the masonry facing and backing are so bonded as to exert common action under load;

fire partition means a partition constructed in accordance with section 918, for the purpose of restricting the spread of fire or to provide an area of refuge, but not necessarily continuous through all stories nor extended through the roof;

fire wall means a wall constructed in accordance with section 909 for the purpose of subdividing a building or separating buildings to restrict the spread of fire and which starts at the foundation and extends continuously through all stories to and above the roof, except where the roof is fireproof or semifireproof and the wall is carried up tightly against the under side of the roof slab;

foundation wall means a wall below the first floor extending below the adjacent ground level and serving as support for a wall, pier, column or other structural part of a building;

hollow wall of masonry means a wall built of masonry units so arranged as to provide an air space within the wall, and in which the inner and outer parts of the wall are bonded together with masonry units;

non-bearing wall means a wall which supports no load other than its own weight;

panel wall means a non-bearing wall built between columns or piers and wholly supported at each story;

party wall means a wall used or adapted for joint service between two buildings;

veneered wall means a wall having a facing which is not attached and bonded to the backing so as to form an integral part of the wall for purposes of load bearing and stability.

Writing includes printing and typewriting.

Section 200

Written notice shall be considered to have been served if delivered in person to the individual or to the parties intended, or if delivered at or sent by registered mail to the last business address known to the party giving the notice.

Yard means a court that extends along the entire length of a lot line.

Zoning means the reservation of certain specified areas within a community or city for buildings and structures for certain purposes with other limitations such as height, lot coverage and other stipulated requirements.

Section 300

ARTICLE III

CLASSIFICATION OF OCCUPANCIES AND CONSTRUCTION.

SECTION 300. CLASSIFICATION OF OCCUPANCIES.

1. Classes designated. For the purposes of this code, buildings are classified, with respect to occupancy and use, as public buildings, institutional buildings, residence buildings, business buildings, storage buildings, industrial and hazardous buildings.

(a). **Public building** means a building in which persons congregate for civic, political, educational, religious, social or recreational purposes; including among others,

armories	court houses	museums
assembly halls	dance halls	passenger stations
auditoriums	exhibition buildings	recreation piers
bath houses	grandstands	restaurants
bowling alleys	gymnasiums	schools
churches	lecture halls	skating rinks
city halls	libraries	stadiums
club rooms	lodge rooms	theatres
colleges	motion picture theaters	

(b). **Institutional building** means a building in which persons are harbored to receive medical, charitable or other care or treatment, or in which persons are held or detained by reason of public or civic duty, or for correctional purposes; including among others,

asylums	infirmaries	penal institutions
homes for the aged	jails	reformatories
hospitals	nurseries	sanitariums
houses of correction	orphanages	

(c). **Residence building**, except when classed as an institutional building, means a building in which sleeping accommodations are provided; including among others,

apartments	dormitories	multifamily houses
club houses	lodging houses	studios
convents		tenements

(d). **Business building** means a building occupied for the transaction of business, for the rendering of professional services, for the display or sale of goods, wares, or merchandise, or for the performance of work or labor; including among others,

Section 300

bakeries	gasoline service	open air stores
barber shops	stations	power plants
banks	hotels	radio stations
chemical labora-	ice plants	smoke houses
tories	laundries	stores
creameries	markets	telephone exchanges
electric substations	office buildings	television stations
		work shops

(e). **Storage building** means a building for the housing, except for purely display purposes, of airplanes, automobiles, railway cars or other vehicles of transportation, for the sheltering of horses, live stock or other animals, or exclusively for the storage of goods, wares or merchandise, not excluding in any case offices incidental to such uses; including among others,

barns	garages	grain elevators
cold storage	gasoline bulk	hangars
freight depots	stations	storage warehouses

(f) **Industrial building** means a building or parts thereof, in which 5 or more persons are engaged in the fabrication, assembly, manufacturing, or processing of products or materials, except that where such products, materials, or those involved in their manufacture are highly combustible, or explosive, the occupancy shall comply with the requirements for hazardous occupancies when the latter are more restrictive than the corresponding requirements for the industrial classification. Where less than 5 persons are engaged in work as described herein, the occupancy shall be in the business classification.

The industrial classification includes among others the occupancies listed below:

factories	assembly plants	mills
manufacturing	loft buildings	laboratories
plants	processing plants	

(g). **Hazardous building** means a building or parts thereof, used for purposes that involve highly combustible, highly flammable or explosive products or materials which are likely to burn with extreme rapidity or which may produce poisonous fumes or gases, including uses that cause division of material into fine particles or dust subject to explosion or spontaneous combustion, and uses that constitute a high fire hazard because of the form, character or volume of the materials used.

2. **Mixed Occupancy.** Where a minor portion of a building is used for office, study, studio or other similar purpose, the building shall be classified as to occupancy on the basis of the major use. In other cases where a building is occupied for two or more purposes not included in one class, the provisions of this code ap-

Section 301

plying to each class of occupancy shall apply to such parts of the building as come within that class; and if there should be conflicting provisions, the requirements securing the greater safety shall apply.

3. Doubtful classification. In case a building is not specifically provided for, or where there is any uncertainty as to its classification, its status shall be fixed by a duly promulgated rule giving due regard to safety.

SECTION 301. CLASSIFICATION OF CONSTRUCTION.

1. Types designated. For the purposes of this code, construction as used in buildings shall be classified as follows:

- (a). Fireproof Construction.
- (b). Semifireproof Construction.
- (c). Heavy Timber Construction.
- (d). Ordinary Construction.
- (e). Noncombustible Construction.
- (f). Wood Frame Construction.
- (g). Unprotected Metal Construction.

**ARTICE IV
GENERAL RESTRICTIONS**

SECTION 400. ZONING RESTRICTIONS.

The restrictions of the zoning ordinance, if there is such an ordinance, shall not be deemed to be modified by any provisions of this code; and such restrictions shall be controlling except in so far as this code imposes greater restrictions by reason of the type of construction used, in which case the provisions of this code shall control.

SECTION 401. RESTRICTIONS ON CONSTRUCTION WITHIN THE FIRE LIMITS.

1. **General restrictions.** Except as otherwise provided in subsection 5 of this section, no building or structure of wood frame construction or of unprotected metal construction shall be erected within the limits established by law as the Fire Limits.

2. **Alterations.**

(a). Within the fire limits no building or structure of wood frame construction or of unprotected metal construction shall be hereafter increased in height.

(b). Within the fire limits no building or structure of wood frame construction or of unprotected metal construction shall be hereafter extended on any side.

(c). Within the fire limits no other building or structure shall be hereafter extended on any side by wood frame construction or unprotected metal construction.

(d). Nothing in this section shall prohibit other alterations within the fire limits; provided there is no change of occupancy to a class of occupancy otherwise prohibited. (See Section 102.2.)

3. **Moving buildings.** No building of wood frame construction or unprotected metal construction shall hereafter be moved from without to within the fire limits or within the fire limits.

4. **Doubtful location.** A building or structure shall be deemed to be within the fire limits if one-third or more of the area of such building or structure is located therein.

5. **Exceptions.** Nothing in this section shall prohibit within the fire limits and subject to the specified limitations, the erection of new buildings or structures, nor the extension or enlargement of heretofore erected buildings or structures, of wood frame construction or unprotected metal construction, as follows:

Section 402

(a). Parking lot offices, real estate offices or similar business structures, of unprotected metal construction, not exceeding 250 square feet in area, nor more than one story in height and located at least 10 feet from lot lines.

(b). A building of wood frame construction or of unprotected metal construction occupied exclusively as a private garage or stable, not more than one story in height nor more than 750 square feet in area, located on the same lot with a dwelling; provided that such building shall be placed at least 10 feet from the lot lines of adjoining property.

(c). Outhouses not more than 8 feet in height nor more than 100 square feet in area when located 10 feet from lot line.

(d). Greenhouses not more than 15 feet in height erected on the same lot with and accessory to a dwelling or a store.

(e). Sheds open on the long sides, not more than 15 feet in height nor more than 500 square feet in area, located at least 10 feet from buildings and from adjoining lot lines.

(f). Builders' shanties for use only in connection with a duly authorized building operation and located on the same lot with such building operation, on a lot immediately adjoining, on an upper floor of the building under construction, or on a sidewalk shed.

(g). Coal tipples, ice houses, material bins, trestles and water tanks, when built of planking and timbers of the dimensions specified for heavy timber construction.

(h). Fences not exceeding 10 feet in height.

(i). Display signs as provided in section 403-8a, and Article XVIII.

(j). Cooling towers as provided in section 923-7.

(k). Roofs over parking lots, of unprotected metal construction, where roof is at least 10 feet above the floor, and every 40 feet there is an open ventilation area 6 feet wide extending either the full length or the full width of the roof.

SECTION 402. SPECIAL OCCUPANCY REQUIREMENTS.

1. Institutional buildings.

(a). Institutional buildings for occupants involuntarily detained shall be of fireproof construction or semi-fireproof construction.

(b). Institutional buildings for occupants which are not involuntarily detained, when of other than fireproof construction or semi-fireproof construction, shall not exceed two stories in height and shall have floors and partitions with fire resistance

Section 402

ratings of not less than one hour and with fire retardant ceilings under roofs, and if of wood frame construction shall not exceed one story in height nor 2500 square feet in area.

2. Theatres and motion picture theatres.

(a). Theatres and motion picture theatres shall be of fireproof construction or semi-fireproof construction, except that portions of such buildings not over 1 story or over 45 feet in height may have combustible roof construction if protected by fire retardant ceilings.

(b). No theatre or motion picture theatre shall be located within or attached to a building of other occupancy unless it is separated from such other occupancies by walls and floors of non-combustible construction having fire resistance ratings of not less than 3 hours.

3. Schools, churches, colleges, assembly halls, dance halls, bowling alleys, and auditoriums over one story in height, shall have floors and structural members of not less than one-hour fire resistance.

4. Wall and ceiling finish. In the exit ways from public buildings and institutional buildings, and all places of assembly, no combustible material shall be used as interior wall or ceiling finish which is of such a nature that the flame spread over its surface is more than 50 according to the "Fire Hazard Classification of Building Materials" of Underwriters' Laboratories, Inc., or which has a classification of fire retardent or better according to the test method of Federal specifications, S S-A-118.

5. Business and residence separation. In buildings of other than fireproof or semi-fireproof construction portions classified as of business occupancy shall be separated from portions classified as of residence occupancy by partitions having a fire resistance rating of not less than one hour and by fire retardant ceilings, unless the business portion is sprinklered.

6. Separation of dwellings. Walls or partitions separating 2 or more dwellings of other than fireproof or semi-fireproof construction shall consist of a form of construction having a fire resistance rating of not less than 1 hour.

7. Partitions in multifamily houses. In multifamily houses partitions separating apartments or apartments from hallways or apartments from other occupancies and partitions separating stores from hallways or other occupancies shall have a fire resistance rating of not less than one hour, with openings equipped with approved fire doors or with substantial metal or metal covered doors or solid wooden doors of the flush type of nominal thickness not less than 1 $\frac{3}{4}$ -inch.

Sections 403—404

SECTION 403. HEIGHT RESTRICTIONS.

1. **New buildings.** Except as may be otherwise provided in subsection 3 of this section, no building hereafter erected shall exceed in height the limits fixed by table 403.

2. **Alterations.** No building shall hereafter be altered so as to exceed the limits of height fixed by table 403.

3. Exceptions.

(a). For the purpose of this section, the following appurtenances shall not be deemed parts of buildings: church spires, tanks and their supports, roof structures, chimneys, signs attached to the building, radio masts, water cooling towers for air conditioning or other apparatus, and parapets that do not extend more than 4 feet above the roof surface at their point of contact.

(b). Outside the fire limits, public buildings, business buildings, or storage buildings may, in the discretion of the Commissioner of Insurance, be erected to greater heights than fixed by this section.

SECTION 404. AREA RESTRICTIONS.

1. **New Buildings.** Except as otherwise provided in subsection 4 of this section, the building area permitted without suitable subdivisions by fire walls shall be limited as indicated in Table 404.

2. **Street.** Under this section a street shall be deemed to include any avenue, boulevard, street, alley or lane, 20 feet or greater in width, or any court, parking space or yard, with direct connection to a street, and not less than 20 feet wide. Such court, parking space or yard shall be the property of the owner of the building and shall not be enclosed or roofed over.

3. **Alteration.** No building shall be hereafter altered so as to exceed in area in any story the limits fixed in this section.

4. Area Modification.

(a) Area Increase for Sprinklers

The allowable floor areas for business, industrial and storage buildings specified in Section 404 and in Table 404 may be increased by 100 per cent if the building is equipped throughout with automatic sprinklers, except that such increase shall not be permitted in buildings where, because of occupancy or conditions, sprinkler equipment is a requirement of the Code, or where in the opinion of the Insurance Commissioner the nature of the hazard involved is such that sprinkler equipment does not substantially reduce the fire hazard or where application of water may cause an explosion.

TABLE 403—BUILDING HEIGHT LIMITS

See section 401 for restrictions on wood frame construction and unprotected metal construction within the fire limits
 See section 402 for height limits for certain special occupancies.
 See section 1702 for sprinkler requirements based on occupancy.
 See section 403—8 (b).

CLASSIFICATION OF OCCUPANCY	FIRE-PROOF	SEMI-FIREPROOF	NONCOM-BUSTIBLE 2	NONCOM-BUSTIBLE 1	HEAVY TIMBER	ORDINARY	WOOD FRAME	UNPROTECTED METAL
Public	No Limit	75 Feet (Note A)	3 Stories 40 Feet (Note B)	3 Stories 40 Feet (Note B)	3 Stories 40 Feet	3 Stories 40 Feet (Note B)	1 Story 25 Feet	1 Story 25 Feet
Institutional	No Limit	75 Feet	2 Stories 35 Feet	2 Stories 35 Feet	2 Stories 35 Feet	2 Stories 35 Feet	1 Story 35 Feet	1 Story 35 Feet
See section 402 for special occupancy requirements.								
Residence	No Limit	No Limit	3 Stories 45 Feet (Note C)	3 Stories 45 Feet (Note C)	75 Feet	3 Stories 45 Feet (Note C)	2 Stories 35 Feet (Note H)	2 Stories 35 Feet (Note H)
Business	No Limit	75 Feet (Note D)	4 Stories 50 Feet	4 Stories 50 Feet	75 Feet	4 Stories 50 Feet	2 Stories 35 Feet	2 Stories 35 Feet
Storage	No Limit (Note E)	6 Stories 75 Feet (Note F)	2 Stories 35 Feet	2 Stories 35 Feet	3 Stories 35 Feet (Note G)	2 Stories 35 Feet (Note G)	1 Story 25 Feet	1 Story 25 Feet

Section 404

	No Limit	8 Stories 100 Feet (Note F)	3 Stories 35 Feet	3 Stories 35 Feet	3 Stories 35 Feet	2 Stories 35 Feet	1 Story 25 Feet	1 Story 25 Feet
Industrial								
See section 403—8—(b) and Section 404—(d)								
Hazardous	Heights cannot be established due to various types of hazardous uses. Hazardous locations must be protected in accordance with good practices as recommended in Section 1504. (See section 403—8—(b) and Section 404—(d).)							

Note A. No limit if less than 100 persons above 75 feet

Note B. Churches: 2 Stories, 45 feet

Schools: 2 Stories

Note C. With 2 hour non-combustible first floor, height may be increased to 4 stories or 55 feet; in multi-family building with 2 hour noncombustible first floor and other floors of one hour fire resistance and with fire partitions sub-dividing floors into areas not exceeding 3500 square feet the height may be 5 stories or 65 feet.

Note D. Office buildings not limited.

Note E. Automatic sprinklers required when height exceeds 6 stories.

Note F. Automatic sprinklers required when height exceeds 4 stories.

Note G. Automatic sprinkler installation will allow height increase to 50 feet.

Note H. Dormitories: 1 story.

TABLE 404--AREA LIMITS PER FLOOR OF BUILDINGS IN SQUARE FEET

OCCUPANCY CLASSIFICATION	FIRE-PROOF	SEMI-FIREPROOF	NONCOM-BUSTIBLE 2	NONCOM-BUSTIBLE 1	HEAVY TIMBER	ORDINARY	WOOD FRAME	UNPROTECTED METAL
*Public	No Limit	No Limit	(3) 6,500 (2) 8,000 (1) 10,000	(3) 7,500 (2) 10,000 (1) 15,000	(3) 7,500 (2) 10,000 (1) 15,000	(3) 6,500 (2) 8,000 (1) 10,000	(1) 4,000	(1) 4,000
Institutional	No Limit	No Limit	(2) 5,000 (1) 7,500	(2) 10,000 (1) 15,000	(2) 10,000 (1) 15,000	(2) 5,000 (1) 7,500	(1) 3,000	(1) 3,000
Residence	No Limit	No Limit	(3) 6,500 (2) 8,000 (1) 10,000	(3) 6,500 (2) 8,000 (1) 10,000	(3) 6,500 (2) 8,000 (1) 10,000	(3) 6,500 (2) 8,000 (1) 10,000	(2) 3,000 (1) 4,000	(2) 3,000 (1) 4,000
*Business	No Limit	No Limit	(4) 6,000 (3) 7,500 (2) 7,500 (1) 10,000	(4) 10,000 (3) 10,000 (2) 10,000 (1) 15,000	(5) 10,000 (4) 10,000 (3) 15,000 (2) 15,000 (1) 20,000	(4) 6,000 (3) 7,500 (2) 7,500 (1) 10,000	(2) 3,000 (1) 5,000	(2) 3,000 (1) 5,000
*Storage	No Limit	(6) 18,000 (5) 19,000 (4) 20,000 (3) 22,000 (2) 24,000 (1) 25,000	(2) 5,000 (1) 10,000	(3) 5,000 (2) 10,000 (1) 15,000	(3) 5,000 (2) 10,000 (1) 20,000	(2) 5,000 (1) 10,000	(1) 5,000	(1) 5,000

Section 404

*Industrial	No Limit	(8) 21,000 (7) 22,500 (6) 24,000 (5) 25,500 (4) 27,000 (3) 28,500 (2) 30,000 (1) No Limit	(3) 10,000 (2) 15,000 (1) 20,000	(2) 7,500 (1) 10,000	(3) 10,000 (2) 15,000 (1) 20,000	(2) 7,500 (1) 10,000	(1) 6,500	(1) 6,500

See section 404—(d)

Hazardous
Areas cannot be established due to various types of hazardous uses.
Hazardous locations must be protected in accordance with good practice as recommended in Section 1504.
See section 404—(d).

*The limiting areas of this section for public, business, storage and industrial occupancies may be increased by 50 per cent when the building has frontage on two streets and by 100 per cent when it has frontage on three or more streets. The same allowances may be made when the building is not located on a street line, but is directly accessible to fire apparatus on two or more sides. This area increase shall not apply to Public buildings exceeding one story in height.

Note: (1) The numerals in parenthesis refer to height of building in stories. Please see Table 404 and definition of area and height in Section 200.

(2) Please see Table 700 for fire protection of structural parts for different types of construction.

Section 404

(b) Area Increase for One-Hour Fire Resistance

Where the interior of a building, including roof, floors over all usable spaces, and their supports, also walls and partitions, is provided with 1-hour fire protection the area limit specified in Table 404 may be increased by 33 $\frac{1}{3}$ per cent if the building is of ordinary or wood frame or unprotected metal construction and by 50 per cent if the building is of non-combustible construction.

(c) Area Increase for Tobacco Warehouses

Outside the fire limits the area between fire walls of one story tobacco storage and sales warehouses of non-combustible, ordinary, frame and unprotected metal construction may be increased as per the following table when separated on all sides by the following distances from the lot line or an existing building on the same lot and further provided the building is located at least one hundred feet from fire district.

Distance	Area
75 Feet.....	25,000 Square Feet
100 Feet.....	100,000 Square Feet

All property in the required distance must be owned or controlled by the owner of the proposed building or in the form of established streets or alleys.

(d) Area Increase for Buildings Remotely Located

Outside the congested areas of the city, when a hazardous condition is not created thereby, the area of a one-story building used for business, storage or industrial occupancy, may be increased in excess of the areas fixed by this section in the discretion of the Commissioner of Insurance provided the following conditions are met:

1. Proper safeguards must be taken in connection with hazardous materials and processes (see Section 1504).
2. The building must be equipped with approved automatic sprinklers throughout.
3. The distance of travel to an exit or protected exitway passage from any part of the building cannot exceed that specified in Article VI. In such buildings, sufficient exitways to accommodate all the occupants shall lead to the outside of the building on each of two sides or more.
4. Curtain boards or draft stops must be installed as required by enforcing authority.
5. Building must be surrounded on all sides by streets or public places of width not less than specified in the following table.

Section 405

WIDTH OF SEPARATION

<i>Types of Building</i>	<i>Minimum Width of Separation</i>
Fireproof Construction.....	50 feet
Semi-Fireproof Construction	60 feet
Non-Combustible Construction	90 feet
Heavy Timber Construction.....	90 feet
Ordinary Construction	100 feet

SECTION 405. STREET ENCROACHMENTS.

1. **General.** Except as otherwise provided in this section, no part of a building hereafter erected or of an enlargement of a building heretofore erected shall project beyond a street line or a building line.

2. **Projections removable.** A part of a building permitted by subsection 4 of this section to project beyond a street line or building line shall be so constructed that its removal may be made without causing the building to become structurally unsafe.

3. **Structural support.** No part of a building hereafter erected or of an enlargement of a building heretofore erected, that is necessary for structural safety, shall project beyond a street line or building line, but this shall not be deemed to prohibit the projection beyond the street line or beyond the building line within the street line, to the extent of not more than 12 inches, of the footings of street walls; provided such projecting parts of footings are not less than 8 feet below curb level.

4. **Permissible projections.** Under the conditions prescribed in this section and within the limitations specified herein, the following projections shall be permissible, it being understood that when a building line has not been established the street line shall control.

(a). The main cornice, meaning thereby a moulded projection at or near the top of a wall that faces on a street, may project beyond the building line not more than 3 feet; provided such main cornice is not less than 12 feet above curb level at all points.

(b). Cornices of show windows and porches, including metal awning covers, may project beyond the building line not more than 15 inches.

(c). Mouldings, belt courses, lintels, sills, architraves, pediments and similar projections of a decorative character, may extend beyond the building line not more than 4 inches when they are less than 10 feet above curb level, and not more than 10 inches when they are 10 feet or more above curb level.

(d). Columns, pilasters and other similar ornamental projections, including their mouldings and bases, erected for esthetic

Section 405

reasons, may project beyond the building line not more than 12 inches.

(e). Rustications and quoins may project beyond the building line not more than 4 inches.

(f). Base courses may project beyond the building line not more than $1\frac{1}{4}$ per cent of the width of the street but not more than 10 inches in any case; provided they do not extend more than 5 feet above curb level.

(g). No door shall be hung hereafter so as to project, when fully open, more than 12 inches beyond the building line.

(h). Marquises at entrances to buildings may extend beyond the street line and across the sidewalk to the curb line; provided they are not less than 10 feet above the curb level at all points, and, within the fire limits, are constructed of iron and glass or other noncombustible materials. They shall be securely supported from the building, and shall be properly drained.

(i). Drop awnings, attached to buildings, may extend beyond the street line but not nearer than 18 inches to the curb line; provided that, when let down to their full extent, they are not less than 8 feet above the sidewalk at all points.

(j). Fire escapes and balconies to fire towers or other required exits, constructed of steel or other noncombustible material, may project beyond the building line not more than 6 feet; but no part of such fire escapes or balconies shall be less than 12 feet above the sidewalk; provided that nothing in this section shall prevent the use, in connection with permissible fire escapes, of movable stairs to the sidewalk, so arranged that they are more than 12 feet above the sidewalk when not in actual use.

(k). Areas may project beyond the building line not more than 4 feet; provided that every such area shall be covered over at the street level by an approved grating of metal or other noncombustible material.

(l). Vaults, entirely below the sidewalk level, may extend beyond the street line but not beyond the curb line; provided that every such vault shall be roofed over at the street level by approved masonry, reinforced concrete or steel beams with masonry arches.

(m). Openings in the roofs of vaults under street surfaces shall be provided with substantial covers of noncombustible materials, flush with the top surface and constructed to prevent persons from slipping thereon. Covers shall be maintained normally closed, and when open for use shall be fully guarded to prevent accidents.

Section 405

(n). Glass used in vault lights shall not exceed 16 square inches for one light and shall be of such design and shape as will meet the approval of the city building inspector.

(o). Exterior hose connections for fire extinguishing equipments, and fresh air inlets, hereafter installed, shall be set inside the building line; or in recesses in the street walls when such walls are on the building line; or they may project not more than 12 inches beyond the building line through the street wall at least 2 feet above the street level; or they may be placed in the angle made by the street wall with a pilaster or other permissible projection outside the building line.

5. **Limitation.** Nothing in this section shall be deemed to authorize a projection beyond the street line or building line that is prohibited by the zoning ordinance or by other law or ordinance.

6. **Permits revocable.** Permission, expressed or implied in the provisions of this section, to construct a building so as to project beyond the street line or building line is revocable by the municipality at will.

7. **Alterations.** No change or enlargement shall be made to a part of a building projecting beyond the street line or building line, except in conformity with the provisions of this code for new construction.

8. **Existing encroachments.** Heretofore erected parts of buildings which project beyond the street line or building line may be maintained as constructed until their removal is directed by the municipality.

**ARTICLE V
LIGHT AND VENTILATION**

SECTION 500. GENERAL

1. **New buildings.** For the purpose of providing adequate light and ventilation, every building hereafter erected, shall be constructed, arranged and equipped to conform to the provisions of this article.

2. **Alterations**

(a). No building shall hereafter be altered nor rearranged so as to reduce the size of a room or the amount of window space to less than that required for buildings hereafter erected, or so as to create an additional room, unless such additional room is made to conform to the requirements for rooms in buildings hereafter erected, except that such rooms may be of the same height as existing rooms in the same story.

(b). No building shall hereafter be enlarged, nor shall the lot on which it is located be diminished so that the dimensions of a required court shall be less than prescribed for buildings hereafter erected.

3. **Limitation.** Nothing in this article shall be construed to modify the provisions of any other ordinance, or of any rule authorized by law or ordinance, regulating yards, courts or other open spaces; but whenever the provisions of this article require greater yards, courts, or open spaces than prescribed in such ordinance or rule the provisions of this article shall control.

4. **Streets.** For purposes of this article, the term "street" shall be deemed to include railroad rights-of-way, parks, or waterways, 20 feet or more in width.

SECTION 501. ROOMS.

1. **Habitable rooms.**

(a). Every habitable room shall be provided with natural light and ventilation by one or more windows, opening directly on a street or a court conforming to section 506.

(b). Such rooms shall be not less than 7 feet wide in any part, and shall contain not less than 70 square feet of gross floor area. Such rooms shall have a clear height feet of not less than 7 feet 6 inches for at least 60 square feet of floor area.

(c). When kitchens serving dwelling units are completely enclosed, the gross floor area shall be not less than 60 square feet and not less than 90 square feet when dining space is in-

Section 501

cluded, except that in dwellings having no bedrooms the gross area of the kitchen shall be not less than 50 square feet. Kitchens not completely enclosed shall conform to the requirements for alcoves unless separately lighted and ventilated as required for habitable rooms.

2. Other rooms.

(a). Every room, other than a habitable room, used or occupied by persons, except storage rooms with infrequent occupancy, shall be provided with one or more windows or ventilating skylights opening directly on a street or on a court conforming to the requirements of this article; or such rooms shall be provided with an approved means of mechanical ventilation as prescribed in this article.

(b). In mezzanine spaces, which are open to and form a part of another room, the area of such mezzanine space shall be added to the floor area of the room in which it is located in computing the window area required for both spaces.

3. Public buildings. Every room used as an auditorium or for public assembly, and every other room, except a habitable room, that is not provided with windows opening directly on a street or on a court as prescribed in this section for business and work-rooms, shall be provided with an approved system of mechanical ventilation as prescribed in this article, unless the space within such rooms exceeds 100 cubic feet for each occupant and windows having an aggregate area of not less than 10 per cent of the floor surface, one-half of which is openable, and opening on a street or court, are provided on at least 2 sides of the room.

4. Rooms in institutional buildings. In institutional buildings every room shall be provided with natural light by one or more windows opening on a street or on a court conforming to the requirements of this article, and with air by windows as required for habitable rooms or by an approved system of mechanical ventilation as prescribed in this article; provided that in jails and other detention buildings the opening on such street or court of the windows of cells or similar rooms may be indirect.

5. Bathrooms and toilet compartments. Every bathroom and every room containing one or more waterclosets or urinals, shall be provided with ventilation by one or more windows opening on a street or on a court conforming to the requirements of this article; or on a vent shaft which extends to and through the roof or into a court conforming to the requirements of this article; or by a separate duct of noncombustible and corrosion resistant material, not less than 72 square inches in cross-section, extending independently of any duct used for other purposes to and above the roof; or by a ventilating skylight; or by an approved means of mechanical ventilation as prescribed in this article.

Section 501

6. **Service pantries.** Service pantries except in dwellings and in apartments, shall be ventilated as prescribed in this section for bathrooms.

7. **Alcoves.** Any alcove opening off a habitable room, unless separately lighted and ventilated, shall be included as part of that room in computing the amount of window area required. The alcove shall have an unobstructed opening between it and the main room of at least 80 per cent of the wall area of the common wall, measured on the alcove side, unless it is separately lighted and ventilated as prescribed for habitable rooms.

8. **Stairways and corridors.**

(a). Every stairway, public hall or corridor in multifamily houses and in institutional buildings shall be ventilated either by one or more windows opening directly on a street or on a court conforming to the requirements of this article or ventilated by mechanical means approved by the building official or provided with natural ventilation to the outer air by means of a system of vent flues not less than 12 by 12 inches in size approved by the building official. All public halls and vestibules mechanically ventilated shall be equipped for artificial lighting and shall be kept properly lighted at all times.

(b). If windows are used to provide such light and ventilation, there shall be at least one window or ventilating skylight for every 20 feet of length or fraction thereof, unless a window is placed at the end of such hall or corridor so that it will adequately light the public hall or corridor for its entire length.

(c). Every recess or return, the depth or length of which exceeds twice the width of the hall or corridor, that is shut off from any other part by a door or doors, shall be deemed a separate hall or corridor within the meaning of this section.

9. **Rooms having special hazards.** Unless otherwise provided for by law or duly authorized rules, rooms in which, by reason of use or occupancy, dust, fumes, gases, vapors or other noxious or deleterious impurities tending to injure the health of occupants or to create a fire hazard, exist or develop, shall be provided with an approved system of ventilation to remove effectually such impurities during occupancy.

10. **Rooms below grade.** Every room, other than a habitable room, the ceiling of which is below grade or is less than 4 feet above grade and which is frequented by the public or in which 5 or more persons are regularly employed or congregate, shall, unless provided with windows as required for habitable rooms, be provided with approved means of mechanical ventilation as prescribed in this article.

Sections 502—503

11. Access to rooms and waterclosets.

(a). In multifamily houses hereafter erected or altered access shall be had to living rooms, kitchens and bedrooms without passing through a bedroom.

(b). Access without passing through a bedroom shall also be provided to at least one water closet, unless every bedroom has direct connection with a water closet or a bathroom having water closet accommodation.

SECTION 502. WINDOWS.

1. **Glass area.** The aggregate glass area of windows required by this article shall be not less than 1/10 of the floor area of the room served by them; provided that in habitable rooms such glass area shall be not less than 10 square feet, and in bathrooms it shall be not less than 3 square feet.

2. **Openings.** Windows or other openings required for ventilation shall have an aggregate openable area of at least 50 percent of the glass area required for lighting.

SECTION 503. VENT SHAFTS.

1. **Size.** Vent shafts required by this article, shall have a cross-sectional area of not less than 1/5 of a square foot for every foot of height of shaft, but not less than 9 square feet in any case. No such shaft shall be less than 2 feet in its least dimension.

2. **Skylights.** Unless open to the outer air at the top for its full area, such shaft shall be covered by a skylight glazed with plain glass not to exceed 1/8 inch in thickness and protected with a wire screen as specified in section 923-4 and having a net area of fixed louvre openings equal to the maximum required shaft area.

3. Air Intakes.

(a). Such shafts shall be connected with a street, alley or court conforming to the requirements of this article by a horizontal intake at a point below the lowest window opening on such shaft.

(b). Such intake shall have a minimum unobstructed cross-sectional area of not less than 3 square feet with a minimum dimension of 12 inches.

(c). The openings to the intake shall be not less than one foot above the bottom of the shaft and the street surface or bottom of court, at the respective ends of the duct or intake and shall be protected by substantial screens of corrosion resistant material having a mesh not larger than 3/4 inch.

(d). Such intake shall be constructed of noncombustible, corrosion resistant material.

SECTION 504. VENTILATING SKYLIGHTS.

Skylights installed to meet the requirements of this article shall be glazed with plain glass not to exceed $\frac{1}{8}$ inch in thickness and shall have glass area not less than required for the windows they replace and protected with wire screens as specified in section 923-4. They shall be equipped with movable sashes or louvers of an aggregate net area not less than required for openable parts in the windows they replace, or with approved ventilation of equal efficiency.

SECTION 505. MECHANICAL VENTILATION.

When mechanical ventilation is required, or is permitted as an alternative, the system shall be designed and constructed in accordance with generally accepted good practice, to provide the necessary changes of air. Such systems shall be capable of supplying outside air at a rate of not less than 10 cubic feet per minute per person, based on number of occupants determined in accordance with section 602.

SECTION 506. COURTS.

1. Width.

(a). Every court or yard if light and ventilation are dependent on such, required by this article to serve habitable rooms shall have a width, at any given level, of not less than $\frac{1}{3}$ of the height of such court, but not less than 6 feet.

(b). Every other required court shall have a width at any given level, of not less than $\frac{1}{4}$ of the height of such court, but not less than 6 feet.

2. Area. The cross-sectional area of a required court shall be not less than $1\frac{1}{2}$ times the square of its required least dimension.

3. Street Widths. For the purpose of this article a street shall be deemed a court. In case such street is of less width than required for a court, the building or that part dependent thereon shall be set back from such street sufficiently to provide the required width, considering the street as part of the court.

4. Intakes. Every court of less than 300 square feet area serving one or more habitable rooms, that does not open for its full height on one or more sides on a street, alley or yard shall be connected at or near the bottom with a street, alley or yard by a horizontal intake or passage. Such intake or passage shall be constructed with walls, floors and ceilings having a fire resistance rating of not less than one hour, and shall have a cross-sectional area of not less than 10 square feet.

Section 506

5. **Unobstructed.** Every court shall remain unobstructed for its required width and full height, except that ordinary window sills or belt courses, projecting not more than 4 inches from a wall, and drop awnings shall not be deemed obstructions. But this shall not prohibit in the open spaces at the ground level, in the case of dwellings only, permissible garages.

6. **Drainage.** The bottom of every court shall be properly graded and drained, and when required by the building official in the interest of public health, shall be paved with concrete or other suitable material and connected with a public sewer.

7. **Accessibility.** Every court that is not otherwise accessible at the bottom, shall be made accessible by a door or other means to enable it to be properly cleaned.